



INSTALLATION INSTRUCTIONS

Part Number 33-2056

This filter fits: **See current K&N catalog for complete listing**

FREE K&N DECAL** To register your warranty, please see us online at knfilters.com/register. **FREE K&N DECAL

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modifications will be required. However the following procedure **MUST** be followed to ensure a proper fit and seal of the K&N Air Filter.

Installation

- 1) Disconnect the intake hose from the airbox lid.
- 2) Remove the airbox lid.
- 3) Remove the filter element from the airbox base.
- 4) Wipe out any dust or dirt from the airbox lid with a damp rag.
- 5) Double-check that the expanded wire is properly seated into the groove at each end of the filter. There is no need to remove this wire when servicing the K&N Air Filter.
- 6) Install the K&N Air Filter into the airbox base. Be certain that the filter is properly seated into the base with expanded wire facing up.
- 7) Slide the airbox lid over the five tabs on the airbox base and while holding pressure on the lid, hinge it closed. (FIG. 1)
- 8) Re-install the intake hose to the airbox lid.
- 9) Reset the restriction gage by pushing the button on its top. Service the filter at or before 15" of restriction.

These instructions must be followed every time the filter is serviced, otherwise the filter may not seal, and damage to the engine could result.

