INSTALLATION INSTRUCTIONS Part Number: 33-3028 This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* FREE K&N[®] decal To register your warranty, please see us online at knfilters.com/register. FREE K&N[®] decal *

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N Filtercharger[®] seals properly.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

- 1. Carefully lift and remove the engine cover from the vehicle. (Fig 1)
- 2. Release the two indicated airbox clips. (Fig 2)
- 3. Ease the 2 halves of the airbox apart and carefully slide out the original air filter. (Fig 3)
- 4. Remove any debris collected in the bottom of the airbox, (using a vacuum cleaner is good for this). (Fig 4)
- 5. Liberally grease the indicated lip sealing edge of the K&N filter, this is to aid filter fitment. (Fig 5)
- 6. Fit the K&N element into the airbox and slide firmly home. (Fig 6)
- 7. Ensure the 2 parts of the airbox are still connected at the base, then reclip the 2 halves of the airbox together. (Fig 7)
- 8. Refit the engine cover. (Fig 8)

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3



Fig. 4









Continued...









CLEANING:

K&N Engineering, Inc., suggests checking the air filter element periodically for excessive dirt build-up. Depending on your driving conditions, we recommend cleaning your air filter every 50,000 miles. To clean and re-oil, purchase our filter Recharger[®] service kit, part number 99-5050 or 99-5000 and follow the easy instructions.