



INSTALLATION INSTRUCTIONS

Part Number: HA-1020

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® Filtercharger® seals properly.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

1. Remove the stock filter.
2. Wipe out any dirt or dust that may be inside the air filter housing.
3. Apply a layer of the supplied sealing grease on the o-ring around the inlet (**FIGS.1 & 2**)
4. Wipe off any excess grease from the inlet.
5. Install the K&N Filtercharger into the air box. Insert the filter at an angle so that the three posts engage the hinges in the air box. (**FIG 3**)
6. Using the two stock screws, secure the K&N Filtercharger to the air box. (**FIG 4**)
7. Re-install the air box lid to complete the installation.
8. Clean an area on the air box and apply the K&N Stop Decal. The decal will help notify others, who may be working on this vehicle, that this is a washable/re-usable air filter.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3



Fig. 4

CLEANING:

K&N Engineering, Inc., suggests checking the air filter element periodically for excessive dirt build-up. Depending on your driving conditions, we recommend cleaning your air filter every 50,000 miles. To clean and re-oil, purchase our filter Recharger® service kit, part number 99-5050 or 99-5000 and follow the easy instructions.