



INSTALLATION INSTRUCTIONS

Part Number: HA-1120

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® Filtercharger® seals properly.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

- 1.) Remove the 3 screws that secure the airbox. (Fig.1)
 - 2.) Remove the dirty OE filter by removing the 2 screws. (Fig.2)
- NOTE: Due to inconsistencies on the sealing surface, apply a small bead of supplied sealing grease to the sealing surface as shown. (Fig. 3)**
- 3.) Install the K&N air filter and secure using the 2 screws. (Fig.4)
 - 4.) Re-install the air box lid to complete the installation.
 - 5.) With the new K&N® air filter installed, clean an area in an obvious location and apply the K&N Stop Decal. The decal will help notify others servicing the vehicle that this is a re-usable filter.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3



Fig. 4

CLEANING:

K&N Engineering, Inc., suggests checking the air filter element periodically for excessive dirt build-up. Depending on your driving conditions, we recommend cleaning your air filter every 50,000 miles. To clean and re-oil, purchase our filter Recharger® service kit, part number 99-5050 or 99-5000 and follow the easy instructions.