

INSTALLATION INSTRUCTIONS Part Number: HA-5019

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® Filtercharger® seals properly.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

- 1. Remove the OE filter from airbox by removing the 4 screws retaining the airbox lid. (Fig. 1 & 2) **NOTE: remove any dirt and debris that may be present in the filter housing.**
- 2. Remove the 2 screws shown in Fig.3 to remove the air duct. (Fig. 3 & 4)
- 3. Remove the 4 screws holding the OE filter. (Fig. 5 & 6)
 - NOTE: The four screws securing the OE filter onto the air box will not be used with the K&N® Air Filter.
- 4. Align the air box lid over the $K\&N^{\circ}$ filter base and install the included screws using a 3mm allen wrench. (Fig. 7 9)
- 5. Reverse steps 1-4 to complete installation

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



ia 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig 9

CLEANING:

K&N Engineering, Inc., suggests checking the air filter element periodically for excessive dirt build-up. Depending on your driving conditions, we recommend cleaning your air filter every 50,000 miles. To clean and re-oil, purchase our filter Recharger® service kit, part number 99-5050 or 99-5000 and follow the easy instructions.