

INSTALLATION INSTRUCTIONS Part Number: HD-1212

This filter fits: See catalog for current applications

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

Congratulations, you have purchased the fi nest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® air filter seals properly.

INSTALLATION:

- 1. Remove the stock air filter.
- 2. Carefully pry the stock air cleaner cover bracket off of the stock air filter. (Fig. 1)
- 3. Install stock air cleaner cover bracket onto K&N® filter and install screws. (Fig. 2)
- 4. Install the provided gasket onto the stock screws on the back of the K&N® Filter. (Fig. 3)
- 5. Install the K&N® Filter onto the stock air cleaner base and make sure it is completely seated.
- 6. Tighten the stock screws a few threads at a time in a clockwise pattern to insure the K&N® Filter is installed evenly.
- 7. Reinstall the stock air cleaner cover and tighten the screws.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3