



INSTALLATION INSTRUCTIONS

Part Number: SU-4518XD

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter can last many seasons. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® air filter seals properly.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

- 1.) Remove wing bolt from the stock air filter and slide filter out. (Fig.1)
- 2.) Clean all sealing surfaces in the air box housing.
- 3.) Apply the wing bolt into the supplied K&N x-stream top filter. (Fig.2)
- 4.) Install the K&N air filter into the housing (filter can only go in one way). (Fig.3)
- 5.) Install the K&N stream top & wing bolt onto the K&N air filter. (Fig.4)
- 6.) Once wing bolt is hand tight, secure filter is sealed by adding 1 full turn on the wing bolt.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3



Fig. 4

CLEANING:

K&N Engineering, Inc., suggests checking the air filter element periodically for excessive dirt build-up. Depending on your driving conditions, we recommend cleaning your air filter every 50,000 miles. To clean and re-oil, purchase our filter Recharger® service kit, part number 99-5050 or 99-5000 and follow the easy instructions.