



K&N Ultra Premium Full Synthetic SAE 5W-20

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

Issue date: 11/10/2020

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product number and name : 104104- K&N Ultra Premium Full Synthetic SAE 5W-20; 1 Quart

1.2. Recommended use and restrictions on use

Recommended use : Lubricant
Restrictions on use : No additional information available

1.3. Supplier

Distributor

K&N Engineering, Inc
1455 Citrus St.
Riverside, CA 92507
T 1-951-826-4000 or 1-800-858-3333
knfilters.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 Toll-Free USA/CAN

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS labelling

No labelling applicable

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%)	(CAS-No.) 72623-87-1	80 - 90	Asp. Tox. 1, H304

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

K&N Ultra Premium Full Synthetic SAE 5W-20

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Burning produces irritating, toxic and noxious fumes.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

Protective equipment : Refer to section 8.2.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Refer to section 8.2.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool well ventilated place.

Incompatible products : Strong bases. Strong acids. Strong oxidizers.

Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

K&N Ultra Premium Full Synthetic SAE 5W-20

No additional information available

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)

USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m ³)	5 mg/m ³ oil mist
--------------------------------	------------------------------

K&N Ultra Premium Full Synthetic SAE 5W-20

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

ACGIH STEL (mg/m³)

10 mg/m³ oil mist

8.2. Appropriate engineering controls

Appropriate engineering controls : Avoid creating mist or spray. Avoid splashing. Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Use rubber gloves.

Eye protection:

In case of splashing or aerosol production: protective goggles.

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber
Odour	: petroleum
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 185 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.07
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 48.86 mm ² /s @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

K&N Ultra Premium Full Synthetic SAE 5W-20

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

None under normal use.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)

LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: 48.86 mm ² /s @ 40 °C
Likely routes of exposure	: Skin and eye contact. Inhalation.
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.

SECTION 12: Ecological information

12.1. Toxicity

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)

LC50 fish 1	> 100 mg/l
EC50 crustacea	> 10000 mg/l
ErC50 (algae)	≥ 100 mg/l
NOEC (acute)	> 100 mg/kg

12.2. Persistence and degradability

K&N Ultra Premium Full Synthetic SAE 5W-20

Persistence and degradability	Not established.
-------------------------------	------------------

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)

Persistence and degradability	Not readily biodegradable.
Biodegradation	2 – 4 %

12.3. Bioaccumulative potential

K&N Ultra Premium Full Synthetic SAE 5W-20

Bioaccumulative potential	Not established.
---------------------------	------------------

K&N Ultra Premium Full Synthetic SAE 5W-20

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

12.4. Mobility in soil

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)	
Mobility in soil	22 %

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

Not regulated.

Transportation of Dangerous

Goods Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)
Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations


No additional information available

National regulations

K&N Ultra Premium Full Synthetic SAE 5W-20
All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on Taiwan National Chemical Inventory Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

 **WARNING:** This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

K&N Ultra Premium Full Synthetic SAE 5W-20

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Toluene(108-88-3)		X				7000 µg/day
Naphthalene(91-20-3)	X				5.8 µg/day	
ethylbenzene(100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	
Benzene(71-43-2)	X	X	X		6.4 µg/day (oral); 13 µg/day (inhalation)	24 µg/day (oral); 49 µg/day (inhalation)

SECTION 16: Other information

Data sources : European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-statements:

H304	May be fatal if swallowed and enters airways.
------	---


Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	STEL: Short Term Exposure Limits
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average
	WEL: Workplace Exposure Limit

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.